



Lathe Commander 150

High Precision and Easy Operation

- fine-stepped main gear and feed gear
- max. spindle speed 2500 rpm
- Cr alloy gears are hardened and precision-ground
- wide bed with heavy ribbing
- quick-change tool holder included
- central lubrication in the support

\$ 9,870

inc. Position Indicator



Standard Equipment: 3-jaw chuck (6.3"), quick-change tool holder E, coolant system, splatter guard, halogen work lamp, reducing sleeve (MT 5/3), steady rest (MT5), operating tools and operator's manual

Specifications Commander 150			
center width		27.5"	
max. turning diameter			
- over bed		12.6"	
- over support		7.6"	
bed width		8"	
spindle speeds (quantity/range)	rpm	(16) 48 - 2500	
spindle bore		1.6"	
spindle mount (short taper 5) / taper		DIN 55027 / MT 5	
longitudinal feeds	inch/rev	(24) .0008 - 0.025	
transverse feeds	inch/rev	(24) 0.0003 - 0.008	
max. cross-slide travel		6"	
max. top-slide travel		3.3"	
top-slide swivel range			± 90°
tapping	- metric	mm	0.25 - 8
	- Whitworth		2 - 80
	- module		0.008" – 0.16"
	- diametric	DP	5 - 200
tailstock quill taper diameter			MT3 / 1.6"
tailstock quill stroke			3.35"
tailstock cross adjustment			± 0.4"
motor rating / voltage		Hp	3
dimensions			65" x 29" x 50"
weight		lbs	1540
Part No. with position indicator			300 817
Price \$ with position indicator			9,870