



- ribbed machine stand ensures maximum dynamic rigidity and constant precision
- vertical setup table with 8 setup slots allows individual positioning of the sturdy, large work table
- micro-tuning (18 steps) of spindle gears to maintain a constant optimum spindle speed
- fine adjustments of work feeds and rapid feed on all axes ensure maximum versatility and productivity
- the quill can be advanced manually or automatically (3 steps)
- very wide hardened guideways ensure constant accuracy
- ergonomically arranged controls and a swivelling control panel plus standard digital position indicator for maximum operator comfort
- including automatic lubrication system

Specifications WF 4.2			
Working Area			
travel	- X axis		19.5"
	- Y axis		13.5"
	- Z axis		15.5"
table setup area			15.5"x31"
table load capacity (max.)	lbs		660
T-slots (qty x width x spacing)			8x.6"x1.5"
Feed			
rapid feed	- X axis	"/min	47
	- Y axis	"/min	47
	- Z axis	"/min	47
Feed Speed	- X axis	"/min	.4-20
	- Y axis	"/min	.4-20
	- Z axis	"/min	.4-20
Vertical Cutter Head			
spindle speed		rpm	40 - 2000 (18)
spindle mount			ISO/NMTB40
quill stroke			2"
throat			6.5"-20"
spindle nose-to-table distance			.2"-15.5"
head swivel range			±90°
Horizontal Cutter Head			
spindle speed		rpm	40-2000 (18)
spindle mount			ISO 40
spindle axis-to-table distance			1.4" - 17"
Drive Capacities			
main motor rating		Hp	4
motor rating for feed		Hp	2
coolant pump motor rating		Hp	0.1
Dimensions/Weight			
overall dimensions (LxWxH)			72" x 65" x 67"
weight		lbs	5060
Part No.			370 313
Price \$			32,700